

# CX<sup>3</sup> changeover switches, push-buttons, control switches and LED indicators



Technical characteristics [see e-catalogue](#)

Pack	Cat.Nos	Changeover switches	Number of modules
10	4 129 00	<b>Two-way - 250 V~</b> Connection	1
5	4 129 01	<b>Double two-way - 400 V~</b> Connection	2
10	4 129 02	<b>Two way with centre point - 250 V~</b> Connection	1
5	4 129 03	<b>Double two way with centre point - 250 V~</b> Connection	2
10	4 129 04	<b>Switch NO + NC - 250 V~</b> Connection	1

Pack	Cat.Nos	Momentary contact push-buttons	Number of modules
10	4 129 08	<b>Single function push-buttons</b> 1 NO Connection	1
10	4 129 09	1 NC Connection	1
10	4 129 16	<b>Dual functions push-buttons without indicator</b> 1 NO (green push-button) + 1 NC (red push-button) Connection	1
10	4 129 18	<b>Dual functions push-buttons with indicator</b> 1 NO + green LED indicator 12/48 V~/=	1
10	4 129 19	1 NC + red LED indicator 12/48 V~/=	1
10	4 129 20	1 NO + green LED indicator 100/400 V~	1
10	4 129 40	1 NC + red LED indicator 100/400 V~	1

Pack	Cat.Nos	Maintained contact control switches	Number of modules
Conform to IEC 60669-1 Nominal rating 20 A - 250 V~ Compatible with fluorescent lamps (20 AX) Accept prong-type supply busbars			
10	4 129 10	<b>Single function control switches</b> 2 NO Connection	1
10	4 129 11	1 NO + NC Connection	1
10	4 129 12	<b>Dual functions control switches with indicator</b> 1 NO + green LED indicator 12/48 V~/=	1
10	4 129 13	1 NC + red LED indicator 12/48 V~/=	1
10	4 129 14	1 NO + green LED indicator 110/400 V~	1
10	4 129 15	1 NC + red LED indicator 110/400 V~	1

Pack	Cat.Nos	LED indicators	Number of modules
Equipped with non replaceable LED lamps LED life: 100 000 h LED consumption: 0.17 W under 230 V~/ 0.11 W under 24 V~/ Conform to IEC 60947-5-1 Accept prong-type supply busbars			
10	4 129 21	<b>Single - 12/48 V~/=</b> ● Green	1
10	4 129 22	● Red	1
10	4 129 23	● Yellow	1
10	4 129 24	● Blue	1
10	4 129 25	○ White	1
10	4 129 26	<b>Single - 110/400 V~</b> ● Green	1
10	4 129 27	● Red	1
10	4 129 28	● Yellow	1
10	4 129 29	● Blue	1
10	4 129 30	○ White	1
10	4 129 41	<b>Double - 12/48 V~</b> ●● Green/Red	1
10	4 129 31	<b>Double - 110/400 V~</b> ●● Green/Red	1
10	4 129 32	<b>Triple - 230/400 V~</b> ○○○ White	1
10	4 129 33	●●● Red	1
10	4 129 34	●●● Red/Yellow/Green	1
10	4 129 35	●●● Red/Yellow/Blue	1

Pack	Cat.Nos	TX <sup>3</sup> LED indicators - 230 V~	Number of modules
Equipped with non replaceable LED lamps			
12	6 040 77	<b>Single</b> ● Green	1
12	6 040 78	● Red	1
12	6 040 79	● Orange	1