

Osmoz control and signalling units: non-illuminated heads (continued)



0 239 32



0 239 51

Technical characteristics p. 355 and e-catalogue

Supplied with a fixing ring
IP 66, IP 69K
Conform to IEC 60947-5-1

Pack	Cat.Nos	Selector switches (continued)
10	0 239 30	With long handle Black long handle 2 stay-put positions - 45°
1	0 239 31	2 positions with spring-return - 45°
1	0 239 32	2 stay-put positions - 45°
1	0 239 34	2 stay-put positions - 90°
5	0 239 40	3 stay-put positions - 45°
1	0 239 43	3 positions with spring-return to 0 - 45°
		With key Black button
1	0 239 50	2 stay-put positions - 45°
1	0 239 51	2 stay-put positions - 45°
1	0 239 52	2 positions with spring-return - 45°
1	0 239 53	2 stay-put positions - 90°
1	0 239 54	2 stay-put positions - 90° Key free in both positions
1	0 239 60	3 stay-put positions - 45°
1	0 239 61	3 positions with spring-return to 0 - 45°
1	0 239 63	3 stay-put positions - 90° Key free in 3 positions

Osmoz control and signalling units: illuminated heads



0 240 02



0 240 12



0 240 73

Technical characteristics p. 355 and e-catalogue

Supplied with a fixing ring
IP 66, IP 69K (except Cat.No 0 240 73 - IP 66)
Conform to IEC 60947-5-1

Pack	Cat.Nos	Spring return
		Flush
10	0 240 00	○ White
10	0 240 01	● Red
10	0 240 02	● Green
1	0 240 03	● Blue
5	0 240 04	● Yellow
		Projecting
1	0 240 11	● Red
1	0 240 12	● Green
		Twin touch
		Flush/Projecting
		Red engraved "O", green engraved "I"
		IP 66, become IP 67 with mounting accessory IP 67 shroud Cat.No 0 241 96 (p. 320)
5	0 240 73	● Red ● Green

For detailed dimensions, see e-catalogue

