

Mosaic™ Programme mechanisms

German standard multi-support single and multiple socket outlets



Selection chart for boxes, supports and plates **p. 900-901**

| Pack | Cat.Nos | Multi-support single socket outlets - German standard | |
|------|-----------------------|---|---|
| | | For installation in flush-mounting box, surface-mounting box, floor box, column module, desktop multi-outlet extension, office module and trunking 2 modules | |
| 10 | 0 772 11 ¹ | 2P+E with shutters for child protection <input type="radio"/> White - automatic terminals <input type="radio"/> White - with special tap-off screw and 4 mm ² screw terminals <input checked="" type="radio"/> Red - automatic terminals <input type="radio"/> Alu - screw terminals <input type="radio"/> White antimicrobial ⁽²⁾ - screw terminals <input type="radio"/> Green antimicrobial ⁽²⁾ - automatic terminals <input type="radio"/> Orange antimicrobial ⁽²⁾ - automatic terminals <input type="radio"/> Red antimicrobial ⁽²⁾ - screw terminals | |
| 10 | 0 772 13 ¹ | | |
| 10 | 0 772 18 ¹ | | |
| 10 | 0 792 13 ¹ | | |
| 10 | 0 787 02 ¹ | | |
| 10 | 0 772 16 ¹ | | |
| 10 | 0 772 17 ¹ | | |
| 10 | 0 772 20 ¹ | | |
| 10 | 0 772 10 ¹ | | 2P+E without child protection <input type="radio"/> White - screw terminals |
| 10 | 0 772 45 ¹ | | 2P+E angled 45° <input type="radio"/> White - automatic terminals |
| 10 | 0 772 14 ¹ | 2P+E tamperproof <input checked="" type="radio"/> Red - screw terminals To be used with the tamperproof insert Cat.No 0 502 99 | |
| 1 | 0 772 31 | 2P+E "Access Design" Special for disabled persons Simple action on the lever allows easy plug-in or unplug <input type="radio"/> White antimicrobial ⁽²⁾ | |
| 10 | 0 772 19 | 2P+E with cover <input type="radio"/> White antimicrobial ⁽²⁾ - automatic terminals | |
| 10 | 0 772 12 | 2P+E with indicator <input type="radio"/> White antimicrobial ⁽²⁾ - automatic terminals Indicator 230 V - 2.4 mA supplied | |

| Pack | Cat.Nos | Multi-support multiple socket outlets - German standard |
|------|----------|--|
| | | For installation in flush-mounting box, surface-mounting box, floor box, column module, desktop multi-outlet extension and office module Inclined 45° - IK 07 Connection by automatic terminals |
| 10 | 0 772 52 | 2 x 2P+E <input type="radio"/> White <input type="radio"/> White - with indicator 230 V - 2.4 mA (supplied) <input type="radio"/> Alu <input checked="" type="radio"/> Red <input checked="" type="radio"/> Red - with indicator 230 V - 2.4 mA (supplied) <input checked="" type="radio"/> Red - tamperproof. To be used with tamperproof insert Cat.No 0 502 99 <input checked="" type="radio"/> Red - tamperproof, with indicator 230 V - 2.4 mA (supplied). To be used with tamperproof insert Cat.No 0 502 99 |
| 10 | 0 772 90 | |
| 10 | 0 792 82 | |
| 10 | 0 772 72 | |
| 10 | 0 772 91 | |
| 10 | 0 772 81 | |
| 10 | 0 772 92 | |
| 10 | 0 772 53 | |
| 10 | 0 792 83 | |
| 10 | 0 772 73 | |
| 10 | 0 772 82 | |
| 5 | 0 772 54 | 3 x 2P+E <input type="radio"/> White <input type="radio"/> Alu <input checked="" type="radio"/> Red <input checked="" type="radio"/> Red - tamperproof. To be used with tamperproof insert Cat.No 0 502 99 |
| 5 | 0 772 74 | |
| 5 | 0 772 83 | |
| 5 | 0 772 83 | 4 x 2P+E <input type="radio"/> White <input checked="" type="radio"/> Red <input checked="" type="radio"/> Red - tamperproof. To be used with tamperproof insert Cat.No 0 502 99 |
| 5 | 0 772 74 | |
| 5 | 0 772 83 | |
| 10 | 0 502 99 | Tamperproof insert Tamperproof insert for socket Fits directly into the plug |
| 10 | 0 676 63 | Green light for socket outlets 230 V Consumption 2.4 mA To be wired |

1: Can be installed in receptacles for floor sockets (p. 479)
 2: Contains a silver compound to prevent the growth of bacteria on the surface of the plate

Black sockets for columns and pop-up boxes **p. 847**

Sockets for snap-on trunking **p. 810**

Sockets for DLP trunking **p. 826**