

Batibox™

flush-mounting boxes for dry partitions









Installation see e-catalogue

Pack	Cat.Nos		1-gang boxes			
	Depth 40	Depth 50	For 1 module			
20	0 800 40		Drilling diameter 32 mm			
50	0 800 41	0 800 51	For 1 gang or 2 modules Drilling diameter 67 mm For wiring accessories using screws or claws			
	Multi-gang boxes					
			For wiring equipment using screws Drilling diameter 67 mm Supplied with 1 removable divider for accommodating extended functions For 83.5 mm fixing centres			
15	Depth 40 0 800 49	Depth 50	Compatible with: Arteor and Mosaic ranges 3 modules horizontal mounting			
30	0 800 42	0 800 52	For 71 mm fixing centres Compatible with: Arteor, Mosaic, Valena Life/Allure, Niloé, Kaptika 2-gang or 4/5 modules Horizontal or vertical use			
30	0 800 43	0 800 53	3-gang or 6/8 modules Horizontal or vertical use			
30 15	0 800 44 0 800 54		4-gang or 8/10 modules Horizontal or vertical use			
	Universal covers					
			For converting wiring devices boxes into junction boxes or for closing up an existing box Supplied without fixing screws For one-gang or multi-gang boxes			
20	0 801 80		Round cover, Ø85 mm,			
20	0 892 81		for 1-gang box Square cover, 80 x 80 mm, for 1-gang box			
10	0 801 82		Cover for Batibox and Ecobatibox 2-gang box			
			Accessory			
20			ong screw Ø3 mm ength 40 mm			

Pack	Cat.Nos	Junction boxes	
10 10 10 10	0 893 72 0 893 73 0 893 74 0 893 75	Supplied with cover and so Knockout base Box ext. dim. (mm) 115 x 115 x 40 mm 160 x 105 x 40 mm 170 x 170 x 50 mm 230 x 170 x 50 mm	Crews Cover dim. (mm) 135 x 135 mm 190 x 135 mm 195 x 195 mm 225 x 210 mm

Batibox multimedia boxes

Multi-material flush-mounting boxes for connecting wall-mounted LCD or plasma screens Supplied with 2 Mosaic programme 5-module supports for flush-mounting high/low current supports for flush-mounting high/low current functions
(e.g.: 2P+E, TV sockets, HDMI, RCA sockets, etc.)
Supplied without sockets
Can be installed in advance to reserve the future space for a screen
Extra-slim cover with cut-out panel for cable outlet Equipped with a site protective cover
Storage space for cords Equipped with a site protective cover
Storage space for cords
Supplied with retaining bar for cords
Suitable for solid or cavity walls. Depth: 50 mm
0 801 93
Max. capacity: 1 x 5 modules
Dimensions: 142 x 142 mm
Max. capacity: 2 x 5 modules
Dimensions: 285 x 142 mm







